Rochester Wastewater Treatment Facility


Aeration Blower Upgrade Project

Project Drivers

- The aeration process is the highest power demand at a WWTF
- Replacing aeration blowers with more efficient technology would:
 - Reduce energy usage
 - Reduce green house gas emissions

Technology Selection

- Positive Displacement Blowers
 - Low efficiency (~60% at full speed)
 - Limited turndown capacity
 - Noisy
- Turbine Blowers
 - Higher efficiency than PD blowers
 - Gear driven or direct drive
 - Control of air volumetric air flow



Turbine Blower Selection

- Direct Drive Turbine
 - Magnetic or air bearing design
 - Introduced to US market in last 10 years
 - Checkered history of operation
 - Turndown issues
 - Multi-unit operation issues
 - Parts availability a concern
- Gear driven turbine
 - Proven history of reliable operation
 - In market place for over 30 years
 - Recently introduced "smaller" units (~100 hp)
 - Efficiencies in high 80% range across broad range of air flow

Project Highlights


- Power analysis
 - Power monitoring performed before and after installation of new blowers
 - PD blowers 240 amps at 4,000 cfm
 - Siemens blowers 139 amps at 4,000 cfm
 - 42% energy savings
- Blower skids ship fully assembled
 - Dismantle in field to install in basement
 - Reassemble in-place


Project Cost Summary

| | Original | Grant | | |
|-----------------|--------------|--------------|--------------|---------------------|
| Item | Budget | Disbursement | Actual Cost | City Matching Funds |
| Design | \$ 45,000.00 | \$ 50,000.00 | \$60,000.00 | \$10,000.00 |
| | | | | |
| Blower Purchase | \$218,600.00 | \$220,610.00 | \$441,220.00 | \$220,610.00 |
| | | | | |
| Construction | \$130,400.00 | \$123,390.00 | \$172,676.45 | \$49,286.45 |
| | | | | |
| TOTAL | \$394,000.00 | \$394,000.00 | \$673,896.45 | \$279,896.45 |

Estimated payback for single blower ~ 5 years

PRODUCT INTEGRALLY GEARED





P (kw)≈= f (flow, pressure, temperature)


DUAL POINT CONTROL





IGV Position

 $P = f(Q, \Delta p, Ti, \eta is)$



Inlet Temperature

Differential Pressure

Discharge Capacity (DV Position)

How It Began – Evolution of Turblex



INSTALLATIONS





Containerized Units



Installations

