NHPUC NO. 8 - ELECTRICITY DELIVERY2nd-3rd Revised Page 26PUBLIC SERVICE COMPANY OF NEW HAMPSHIRE
Issued in lieu of 1st Superseding 2nd Revised Page 26 Terms and Conditions

Additional Distribution Facilities

Any overhead or underground distribution facilities required to serve a Customer in addition to a pole-mounted transformer and/or an Overhead or Underground Service Drop as defined above, are subject to the charges specified below.

Adding Additional Phases to Existing Overhead Single-phase Facilities

The estimated cost shall be derived based on the Customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads. The estimated cost shall not include the cost associated with any Overhead Service Drops.

<u>Overhead Single-Phase Facilities</u> The estimated cost shall be derived by multiplying the length of the distribution facilities by the average cost per foot of overhead single-phase distribution facilities based on the following schedule of charges. The length of the distribution facilities shall be based on the length of single-phase primary and secondary line to be installed, excluding the length of secondary line to be installed for any Overhead Service Drops.

Effective Dates	Overhead, Single-Phase <u>Average Cost per Foot</u>
November 28, 2013 — March 31, 2014 — April 1, 2014 — March 31, 2015 April 1, 2014 -2015 — Forward	\$20.71 \$21.54 See section "Average Cost per Foot Effective From April 1, 201 42015 – Forward"

Overhead Three-Phase Facilities

The estimated cost shall be derived based on the customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads. The estimated cost shall not include the cost associated with any Overhead Service Drops.

Issued: December 3. 2013 February 24, 2014

Issued by: <u>/s/ Robert A. Bersak William J. Quinlan</u>

November 28, 2013 April 1, 2014 Effective:

Title: Assistant Secretary President and Chief Operating Officer

NHPUC NO. 8 - ELECTRICITY DELIVERY PUBLIC SERVICE COMPANY OF NEW HAMPSHIRE Issued in lieu of 1st Superseding 2nd Revised Page 27 Terms and Conditions

Underground Single-Phase Facilities

The estimated cost shall be derived by multiplying the length of the distribution facilities by the average cost per foot of underground single-phase distribution facilities based on the following schedule of charges and adding the result to the excess cost of any padmounted transformers to be installed. The length of the distribution facilities shall be based on the length of single-phase primary and secondary line to be installed, excluding the length of secondary line to be installed for each Underground Service Drop. The excess cost of a padmounted transformer is the amount by which the cost of a padmounted transformer exceeds the cost of an equivalent pole-mounted transformer. The Company will determine the excess cost on the basis of average cost formulas consistently and equitably applied to all underground installations.

	Underground, Single-Phase
Effective Dates	Average Cost per Foot
November 28, 2013 March 31, 2014	<u>\$15.48</u>
April 1, 2014 – March 31, 2015	\$15.37
April 1, 2014 -2015 – Forward	See section "Average Cost per Foot Effective
	From April 1, 2014- 2015 – Forward"

Underground Three-Phase Facilities

The estimated cost shall be derived based on the customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting, overheads and the excess cost of any padmounted transformers to be installed. The estimated cost shall not include the cost of any Underground Service Drops. The excess cost of a padmounted transformer is the amount by which the cost of a padmounted transformer exceeds the cost of an equivalent pole-mounted transformer. The Company will determine the excess cost on the basis of average cost formulas consistently and equitably applied to all underground installations.

Average Cost per Foot Effective From April 1, 2014-2015- Forward

The Company will update the overhead single-phase and underground single-phase average cost per foot figures for effect on April 1 of each year based upon a sampling of actual line extensions completed in the preceding three calendar years using the methodology contained in the Settlement Agreement in Docket No. DE 08-135 and as approved by the Commission in its Order No. 25,046 dated November 20, 2009. All costs related to the construction of the distribution facilities will be included in the average cost per foot figures, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads.

3rd Revised Page 26 Superseding 2nd Revised Page 26 Terms and Conditions

Additional Distribution Facilities

Any overhead or underground distribution facilities required to serve a Customer in addition to a pole-mounted transformer and/or an Overhead or Underground Service Drop as defined above, are subject to the charges specified below.

Adding Additional Phases to Existing Overhead Single-phase Facilities

The estimated cost shall be derived based on the Customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads. The estimated cost shall not include the cost associated with any Overhead Service Drops.

Overhead Single-Phase Facilities

The estimated cost shall be derived by multiplying the length of the distribution facilities by the average cost per foot of overhead single-phase distribution facilities based on the following schedule of charges. The length of the distribution facilities shall be based on the length of single-phase primary and secondary line to be installed, excluding the length of secondary line to be installed for any Overhead Service Drops.

Effective Dates	Overhead, Single-Phase Average Cost per Foot
April 1, 2014 – March 31, 2015 April 1, 2015 – Forward	\$21.54 See section "Average Cost per Foot Effective From April 1. 2015 – Forward"

Overhead Three-Phase Facilities

The estimated cost shall be derived based on the customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads. The estimated cost shall not include the cost associated with any Overhead Service Drops.

Issued:	February 24, 2014	Issued by: _	/s/William J. Quinlan
			William J. Quinlan
Effective:	April 1, 2014	Title:	President and Chief Operating Officer
			· · ·

3rd Revised Page 27 Superseding 2nd Revised Page 27 Terms and Conditions

Underground Single-Phase Facilities

The estimated cost shall be derived by multiplying the length of the distribution facilities by the average cost per foot of underground single-phase distribution facilities based on the following schedule of charges and adding the result to the excess cost of any padmounted transformers to be installed. The length of the distribution facilities shall be based on the length of single-phase primary and secondary line to be installed, excluding the length of secondary line to be installed for each Underground Service Drop. The excess cost of a padmounted transformer is the amount by which the cost of a padmounted transformer exceeds the cost of an equivalent pole-mounted transformer. The Company will determine the excess cost on the basis of average cost formulas consistently and equitably applied to all underground installations.

Underground, Single-Phase
Average Cost per Foot
\$15.37
See section "Average Cost per Foot Effective
From April I, 2015 – Forward"

Underground Three-Phase Facilities

The estimated cost shall be derived based on the customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting, overheads and the excess cost of any padmounted transformers to be installed. The estimated cost shall not include the cost of any Underground Service Drops. The excess cost of a padmounted transformer is the amount by which the cost of a padmounted transformer exceeds the cost of an equivalent pole-mounted transformer. The Company will determine the excess cost on the basis of average cost formulas consistently and equitably applied to all underground installations.

<u>Average Cost per Foot Effective From April 1, 2015 - Forward</u> The Company will update the overhead single-phase and underground single-phase average cost per foot figures for effect on April 1 of each year based upon a sampling of actual line extensions completed in the preceding three calendar years using the methodology contained in the Settlement Agreement in Docket No. DE 08-135 and as approved by the Commission in its Order No. 25,046 dated November 20, 2009. All costs related to the construction of the distribution facilities will be included in the average cost per foot figures, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads.

Issued:	February 24, 2014	Issued by:	/s/William J. Quinlan
			William J. Quinlan
Effective:	April 1, 2014	Title:	President and Chief Operating Officer

3rd Revised Page 27 Superseding 2nd Revised Page 27 Terms and Conditions

Underground Single-Phase Facilities

The estimated cost shall be derived by multiplying the length of the distribution facilities by the average cost per foot of underground single-phase distribution facilities based on the following schedule of charges and adding the result to the excess cost of any padmounted transformers to be installed. The length of the distribution facilities shall be based on the length of single-phase primary and secondary line to be installed, excluding the length of secondary line to be installed for each Underground Service Drop. The excess cost of a padmounted transformer is the amount by which the cost of a padmounted transformer exceeds the cost of an equivalent pole-mounted transformer. The Company will determine the excess cost on the basis of average cost formulas consistently and equitably applied to all underground installations.

	Underground, Single-Phase
Effective Dates	Average Cost per Foot
April 1, 2014 – March 31, 2015	\$15.37
April 1, 2015 – Forward	See section "Average Cost per Foot Effective
	From April 1, 2015 – Forward"

Underground Three-Phase Facilities

The estimated cost shall be derived based on the customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting, overheads and the excess cost of any padmounted transformers to be installed. The estimated cost shall not include the cost of any Underground Service Drops. The excess cost of a padmounted transformer is the amount by which the cost of a padmounted transformer exceeds the cost of an equivalent pole-mounted transformer. The Company will determine the excess cost on the basis of average cost formulas consistently and equitably applied to all underground installations.

Average Cost per Foot Effective From April 1, 2015 - Forward

The Company will update the overhead single-phase and underground single-phase average cost per foot figures for effect on April 1 of each year based upon a sampling of actual line extensions completed in the preceding three calendar years using the methodology contained in the Settlement Agreement in Docket No. DE 08-135 and as approved by the Commission in its Order No. 25,046 dated November 20, 2009. All costs related to the construction of the distribution facilities will be included in the average cost per foot figures, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads.

Issued: February 24, 2014

Issued by:

William J. Quinlan President and Chief Operating Officer

Effective: April 1, 2014

Title:

3rd Revised Page 26 Superseding 2nd Revised Page 26 Terms and Conditions

Additional Distribution Facilities

Any overhead or underground distribution facilities required to serve a Customer in addition to a pole-mounted transformer and/or an Overhead or Underground Service Drop as defined above, are subject to the charges specified below.

Adding Additional Phases to Existing Overhead Single-phase Facilities

The estimated cost shall be derived based on the Customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads. The estimated cost shall not include the cost associated with any Overhead Service Drops.

Overhead Single-Phase Facilities

The estimated cost shall be derived by multiplying the length of the distribution facilities by the average cost per foot of overhead single-phase distribution facilities based on the following schedule of charges. The length of the distribution facilities shall be based on the length of single-phase primary and secondary line to be installed, excluding the length of secondary line to be installed for any Overhead Service Drops.

Effective Dates

Overhead, Single-Phase Average Cost per Foot

April 1, 2014 – March 31, 2015 April 1, 2015 – Forward

\$21.54 See section "Average Cost per Foot Effective From April 1, 2015 - Forward"

Overhead Three-Phase Facilities

The estimated cost shall be derived based on the customer-specific job requirements and shall include all costs related to the construction of the distribution facilities, including but not limited to design and inspection and construction labor; researching and recording easements; materials; traffic control; tree trimming; blasting and overheads. The estimated cost shall not include the cost associated with any Overhead Service Drops.

Issued: February 24, 2014

April 1, 2014

Effective:

Issued by:

President and Chief Operating Officer

Title: